Wedgetail Accessory Light Mount Grab Handle

Fitting Instruction



Congratulations on the purchase of your Australian made Wedgetail Roof Rack product.

Please read and follow the instructions carefully to ensure correct fitment.

Contact us if any parts appear missing, incorrect, or damaged.

Contact us if any question about the size of platform to ensure the correct fitment

Scan QR code for a fitting demonstration





Tools Required:


Spanner (10 mm)

Hex Key (4mm, 5mm)


Kit Content
















Updated: 15 APR 2024


Wedgetail Accessory Light Mount Grab Handle

Fitting Instruction




1

 Loosely assemble the Light Mount using M8 Bolts and Washers and Channel Nut. Refer to the diagram.




2

 If using Rock Lights, assemble the attachment to Light Mount using M6 Bolt, Washer and Nyloc Nut as shown.




3

Attach the Light (rock light)



4

 Assemble the bracket on the top of the cross bar using bolt, washers, and channel nuts. Refer to the diagram.



NOTE-Ensure the channel nuts are 90 degrees to the channels.



Check fastenings are firmly tensioned at regular intervals.

Do not overtighten, this will preserve the spring washers.

Thank you for your purchase.

Wedgetail by Tradesman Roof Racks

Innovation through Inspiration